



# AC 610

8 - 10 bar

3kW 3.5kW - 600Nℓ/min - 150 ℓ

compressore a secco (privo di lubrificazione ad olio) a 6 cilindri (3+3)  
serbatoio con trattamento interno ALM  
filtro sterilizzante opzionale (99% 0.01 mm)

6 cylinder (3+3), oil-less (without oil lubrication), piston compressor  
tank with ALM internal treatment  
sterilising air filter optional (99% 0.01 mm)

| Articolo<br>Item code | kW  | V        | Hz | assorb. AMP<br>absorbed AMPS | Aria Aspirata<br>Intake air flow<br>(Nℓ/min) | Aria resa a 8 bar<br>Delivered air at 8 bar<br>(Nℓ/min) | Capacità<br>serbatoio<br>Tank Capacity<br>(ℓ) | dB (A)* | peso (Kg)<br>weight (Kg) |
|-----------------------|-----|----------|----|------------------------------|--|---|---|---------|--------------------------|
| 013513                | 3   | (3~) 400 | 50 | 7.4                          | 600  | 295   | 150   | 77      | 137                      |
| 013514                | 3.5 | (3~) 380 | 60 | 9.4                          | 720  | 353   | 150   | 79      | 137                      |

**dimensioni:  
dimensions:**

